



DURA-STRIP PREMIUM CONCRETE COATING REMOVER

DESCRIPTION AND BASIC USE: DURA-STRIP is a premium concrete coating remover designed to quickly remove any type of coating from concrete surfaces without harming the concrete itself. DURA-STRIP works on acrylic, varnish, latex, lacquer, urethane, epoxy and most any type of coating.

BENEFITS: ★Powerful formula for fast stripping ★Does not damage concrete
 ★Easy to use

STORAGE: Store in a cool, dry, shaded area. DURA-STRIP will develop unsafe pressure if stored in hot areas and will boil at 104° F.

COVERAGE: Use approximately as many gallons of DURA-STRIP as gallons of sealer that was applied. If coatings are unknown, use approximately 100 - 200 sq ft per gallon.

APPLICATION: Test a small area for results before application. Roll DURA-STRIP on concrete. Allow to sit for 10 minutes. If surface is exterior, power wash residue away with water. For interior, use a scrub brush and a flat blade. Do small areas of no more than 100 square feet at a time. Stubborn coatings will require multiple applications of stripper. Clean with DURA-CLEAN and rinse with clean water. **NOTE: Timing is critical. Watch for film to lift. Removing too soon will leave coating. If left too long, coating will dry and re-seal.**

CLEAN UP: Clean up tools with water.

PRECAUTION: Use safety glasses, protective gloves, and respirator. Cover all areas of your body. Avoid breathing vapors. Pre-soak with water and cover any plants that may come in contact with DURA-STRIP or its residue.

TECHNICAL DATA:

HMIS:

VOC: standard	93 g/L	Health	2	Flammability	1
Flash Point:	N/A	Reactivity	0	Protection	G

CAUTION: KEEP OUT OF REACH OF CHILDREN. Before using or handling, read the Safety Data Sheet and Warranty. DO NOT TAKE INTERNALLY. Avoid contact with skin and eyes. Wear gloves and aprons to protect skin and wear safety eye goggles, and respirator.

WARRANTY: This product is not for public use and is intended for use by licensed contractors, experienced and trained in the use of these products. It is warranted to be of uniform quality within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the affects or as results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.