

PRO-WAX

WATER BASED ACRYLIC/WAX COPOLYMER

DESCRIPTION AND BASIC USE: PRO-WAX is a water-based, acrylic & wax co-polymer which forms a tough abrasion resistant clear non-yellowing top coat polish to protect existing sealers and finishes. This co-polymer offers excellent gloss and matte finish and can be stripped with conventional wax polish removers. Its toughness protects the existing finish and acts as a sacrificial coating for the hard sealed substrate. PRO-WAX resists scuffs while enhancing the finish below. PRO-WAX also increases slip resistance. PRO-WAX is formulated as follows:

PRO-WAX - provides a high gloss or matte showroom finish

BENEFITS:

- ★Reduces the need to reseal surfaces
- ★Increased slip resistance
- ★Durable scuff resistant coating
- ★Non-yellowing

COVERAGE: 1 gallon jug of Proline PRO-WAX covers approximately 1500 square feet per coat. Two or three coats may be preferred. The rate also may vary greatly depending on the desired finished effect.

PREPARATION: Surface should be clean and sealed. Wax can be applied to recently sealed surface as long as it's completely dry.

APPLICATION: Apply with lamb's wool or microfiber applicator. 2 or 4 initial coats may be preferred. Allow about 45 minutes between coats to dry. Buffing with high speed buffing machine will maximize luster of PRO-WAX. Allow 4 hours to cure and dry before foot traffic resumes. Re-apply as needed.

CLEAN UP: Clean up tools with water.

MAINTENANCE: Cleaning of the polished surface should be accomplished using ONLY water or Pledge Multi-surface cleaner and a soft mop. **DO NOT USE** aggressive cleaning agents, such as citrus-based, ammonia, or 409/Simple Green, bleach cleaners. Using an abrasive cleaning tool will scratch and dull the waxed surface, requiring re-application of PRO-WAX to restore the shine.

TECHNICAL DATA:

HMIS:

| | | | | | |
|---------------|------|------------|---|--------------|---|
| VOC: standard | 0g/L | Health | 1 | Flammability | 0 |
| Flash Point: | N/A | Reactivity | 0 | Protection | B |

CAUTION: KEEP OUT OF REACH OF CHILDREN. Before using or handling, read the Safety Data Sheet and Warranty. DO NOT TAKE INTERNALLY. Avoid contact with skin and eyes. Wear gloves and aprons to protect skin and wear safety eye goggles.

WARRANTY: This product is not for public use and is intended for use by licensed contractors, experienced and trained in the use of these products. It is warranted to be of uniform quality within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the affects or as results of such use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.